

PARTS LIST

INDEX	DESCRIPTION	SPECIFICATION	QTY	INDEX	DESCRIPTION	SPECIFICATION	QTY
1	Hex Bolt	4×6	2	20	Washer	8	1
2	Blocking Board		1	21	Lock Nut	M6	1
3	Pin		1	22F	Circuit Board Component		1
4	Driver Blade		1	22.1	HMI		1
5	Main Body		1	22.2	Button		1
5.1	Screw Set A	M4X8	6	22.3	Light Guide		1
5.2	Board		2	22.4F	PCB		1
5.3	Pin	3X8	2	22.5	Hex Bolt	ST1.9*6	4
5.4	Seat		1	22N	PCB Assy.		1
5.5B	Spring base		1	22.1	HMI		1
5.6	Guide Rod		1	22.2	Button		1
5.7A	Spring		1	22.3	Light Guide		1
5.8A	Spring		1	22.4N	PCB		1
5.9	Gasket		1	22.5	Hex Bolt	ST1.9*6	4
5.10	Piston		1	23	Motor Assy.		1
5.11	Steel Ball	φ5	2	23.1	Gear		1
5.12	Bumper		1	23.2	Screw Set A	M3*8	2
5.13	Base		1	23.3	Motor Cap		1
5.14	Lock Nut	M5	1	23.4	Motor		1
6	LED Light		1	24F	Housing R		1
7	Curved rod		1	24N	Housing R		1
8	Connecting rod		1	25	Hex Bolt	ST2.9X16	13
9	Spring		1	26	Hex Bolt	M4X45	1
10	Switch		1	27	Hex Bolt	M4X50	1
11	Switch		1	28	Screw Set A	M5X20	2
12	Latch		1	29	Magazine Assy.		
13F	Housing R		1	29.1	Screw Set A	M4X8	2
13N	Housing R		1	29.2	Nose Cover		1
14F	Trigger		1	29.3	Curved bar		1
14N	Trigger		1	29.4	No-mar Tip		1
15	Spring		1	29.5	Cover Plate		1
16	Switch		1	29.6	Hex Bolt	M4×14modification	2
17	Trigger		1	29.7	Nose		1
18	Reducer Assy.		1	29.8	Screw Set A	M4×10	1
18.1	Gasket		2	29.9	Screw Set D	M4×10	2
18.2	Gear II		3	29.10	Support		1
18.3	Carrier II		1	29.11	Magazine Cover		1
18.4	Gear III		7	29.12	Steel Bar		1
18.5	Carrier III		1	29.13	Latch		1
18.6	Pin	3.5X8	4	29.14	Spring		1
18.7	Output Shaft		1	29.15	O-ring		1
18.8	Parallel Key	2X2X6	1	29.16	Hex Bolt	M4×14	2
18.9	Hex Bolt	M3X45	4	29.17	Pin		1
18.10	Reducer Cap		1	29.18	Locating Rack		1
18.11	Gear ring sleeve		1	29.19	Guide		2
18.12	Bearing	Inner diameter: 8 Outer diameter: 22 Thickness: 9	1	29.20	Pusher		1
18.13	Ring Gear		1	29.21	Spring		2
19	Cam Assy.		1	29.22	Magazine		1
19.1	Cam		1	29.23	Pin	2.5×10	2
19.2	Sleeve		1	30	Cover Plate		1
19.3	Bearing		1	31	Block		1
19.4	Sleeve		1	32	Screw Set A	M4X12	1
19.5	Bearing		1				

ASSEMBLY DIAGRAM

